

## EARTHWOOL SOFFIT LINERBOARDS

March 2020



### APPLICATIONS



### DESCRIPTION

A range of non-combustible products, available in a variety of surface finishes for the insulation of semi-exposed environments such as open-sided car parks. Earthwool Soffit Linerboard Standard\* has a black tissue facing, providing a neat aesthetic finish. Earthwool Soffit Linerboard Extra has an impact-resistant cement particle board for use when a robust solution is required. \*(130mm and above)

### PERFORMANCE

<b>Thermal</b>	Mineral wool - 0.034 W/mK
Thermal conductivity:	Cement particle board facing - 0.47 W/mK
<b>Fire</b>	Mineral wool - EUROCLASS A1 to BS EN 13501-1
Classification:	Cement particle facing - BS 476 Part 4 Non-Combustible and BS 476 Part 22
<b>Vapour resistivity</b>	Mineral wool - 5.00MN/g.m
Water vapour resistivity:	Cement particle board facing - 200MN/g.m

### BENEFITS

- ✓ Excellent thermal performance
- ✓ Non-combustible A1 Euroclass Reaction to Fire classification
- ✓ Excellent sound absorption characteristics
- ✓ Provides a solution to upgrade thermal performance of existing floors without reducing floor height
- ✓ Can be installed without the need to access areas above the floor.

### SPECIFICATIONS

Thickness (mm)	Thermal conductivity (W/mK)	Thermal resistance (m <sup>2</sup> K/W)	Length (mm)	Width (mm)	Pieces per pack
<b>Earthwool Soffit Linerboard Extra</b>					
220/6	0.034 / 0.47	6.55	1200	600	10
185/6	0.034 / 0.47	5.55	1200	600	12
160/6	0.034 / 0.47	4.80	1200	600	12
130/6	0.034 / 0.47	3.95	1200	600	18
<b>Earthwool Soffit Linerboard Standard</b>					
220	0.034	6.45	1200	600	20
185	0.034	5.40	1200	600	28
160	0.034	4.70	1200	600	32
130	0.034	3.80	1200	600	40
<b>Earthwool Soffit Linerboard Standard (unfaced)</b>					
75	0.034	2.20	1200	600	4
50	0.034	1.45	1200	600	6

All dimensions are nominal

### Bespoke Sizes

Earthwool Soffit Linerboard is available in bespoke dimensions to suit specific thermal and aesthetic requirements in thicknesses from 50 to 270mm.

### CERTIFICATION



challenge.  
create.  
care.

## EARTHWOOL SOFFIT LINERBOARDS

March 2020

### ADDITIONAL INFORMATION

#### Durability

Earthwool Soffit Linerboards are odourless, rot proof, non-hygroscopic, do not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

#### Application

Earthwool Soffit Linerboard is used for the thermal and acoustic insulation of soffits in a wide range of both residential and non-residential buildings. The Rock Mineral Wool element of Earthwool Soffit Linerboard is non-combustible which makes it ideal for the underlining of car parks and garages. Earthwool Soffit Linerboard is available in various facing materials all of which are suitable for applications where it will be installed in exposed or semi-exposed environments. Earthwool Soffit Linerboard Standard (unfaced) is used as a base layer when expanding the thickness of insulation needed.

#### Aesthetics

Earthwool Soffit Linerboards are available with a variety of facings.

- Tough, puncture resistant black tissue facing
- Calcium silicate building board (6mm)
- Unfaced for use as a base layer

Alternate facings are available as a bespoke product upon request and subject to a minimum order quantity.

#### Standards

The rock mineral wool element of Earthwool Soffit Linerboards is manufactured in accordance with BS EN 13162, ISO 50001 Energy Management Systems, OHSAS 18001 Occupational Health and Safety Management Systems, ISO 14001 Environmental Management Systems and ISO 9001 Quality Management Systems, as certified by Bureau Veritas.

#### Environmental

Contains no ozone-depleting substances or greenhouse gases. For further environmental information consult the relevant Environmental Product Declaration, available on our website.

The Rock Mineral Wool element has a BRE generic Green Guide rating of A.

#### Vapour resistivity

Earthwool Soffit Linerboards offer negligible resistance to the passage of water vapour. The rock mineral wool element to all variants having a water vapour resistivity of 5.00MN/g.m. The black tissue face to Soffit Linerboard Standard has a water vapour resistivity of 200 MNs/g.m.

#### Handling and storage

Earthwool Soffit Linerboards are easy to handle and install, and easily cut to size where necessary. They are supplied in polythene wrap which is designed for short term protection only. For longer term protection on site, the product should either be stored indoors, or under cover and off the ground. Earthwool Soffit Linerboards should not be left permanently exposed to the elements.



Knauf Insulation mineral wool products made with ECOSE Technology® benefit from a no added formaldehyde binder, which is up to 70% less energy intensive than traditional binders and is made from rapidly renewable bio-based materials instead of petroleum-based chemicals. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE Technology® contain no dye or artificial colours.

#### Knauf Insulation Ltd

PO Box 10, Stafford Road, St.Helens, Merseyside, WA10 3NS. UK

Customer Service: 0844 800 0135

Technical Support Team: 01744 766 666

Literature: 08700 668 660

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

KINE1522DAT-V0320