

## EARTHWOOL STEELTHERM ROLL 40

March 2018



### APPLICATIONS



### DESCRIPTION

Earthwool SteelTherm 40 Roll is a lightweight, flexible and resilient, non combustible glass mineral wool roll, which is manufactured in 600mm widths and specifically designed for friction fitting between standard light steel frame studs.

### PERFORMANCE

#### Thermal

Thermal conductivity: 0.040 W/mK

#### Fire

Classification: EUROCLASS A1 to BS EN 13501-1

#### Vapour resistivity

Water vapour resistivity: 5.00MNs/g.m

### BENEFITS

- ✓ Euroclass A1 non-combustible
- ✓ Designed specifically for steel frame construction
- ✓ Sized to friction fit between steel studs at 600mm centres
- ✓ Easy to handle and install

### SPECIFICATIONS

Thickness (mm)	Thermal conductivity (W/mK)	Thermal resistance (m <sup>2</sup> K/W)	Length (m)	Width (mm)	Area per pack (m <sup>2</sup> )
150	0.040	3.75	5.55	2x600	6.66
100	0.040	2.50	8.65	2x600	10.38

All dimensions are nominal

### CERTIFICATION



challenge.  
create.  
care.

## EARTHWOOL STEELTHERM ROLL

March 2018

### ADDITIONAL INFORMATION

#### Durability

Earthwool SteelTherm Roll 40 is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

#### Application

Earthwool SteelTherm Roll 40 is designed for the thermal insulation of external walls in steel frame constructions. Earthwool SteelTherm Roll 40 is friction fitted between steel studs and is 600mm wide to suit commonly used stud centres.

#### Standards

Earthwool SteelTherm Roll 40 is manufactured in accordance with BS EN 13162, BS EN ISO 50001 Energy Management Systems, OHSAS 18001 Occupational Health and Safety Management Systems, ISO 14001 Environmental Management Systems, and ISO 9001 Quality Management Systems, as certified by Bureau Veritas.

#### Environmental

Earthwool SteelTherm Roll 40 represents no known threat to the environment and has zero Ozone Depletion Potential and zero Global Warming Potential.

#### Vapour resistivity

Earthwool SteelTherm Roll 40 offers negligible resistance to the passage of water vapour and has a water vapour resistivity of 5.00MN<sub>s</sub>/g.m.

#### Handling and storage

Earthwool SteelTherm Roll 40 is easy to handle and install, being lightweight and easily cut to size, where necessary. Earthwool SteelTherm Roll 40 is supplied in polythene packs which are designed for short term protection only. For longer term protection on site, the product should either be stored indoors, or under cover and off the ground. Earthwool SteelTherm Roll 40 should not be left permanently exposed to the elements.



Knauf Insulation mineral wool products made with ECOSE Technology® benefit from a no added formaldehyde binder, which is up to 70% less energy intensive than traditional binders and is made from rapidly renewable bio-based materials instead of petroleum-based chemicals. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE Technology® contain no dye or artificial colours.

#### Knauf Insulation Ltd

PO Box 10, Stafford Road, St.Helens,  
Merseyside, WA10 3NS. UK

Customer Service: 0844 800 0135

Technical Support Team: 01744 766 666

Literature: 08700 668 660

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

KINE1511DAT

challenge.  
create.  
care.